

### Stainless design. Stellar performance. Superior value.

| Project name: |        |
|---------------|--------|
| Location:     |        |
| Item #:       | _ QTY: |
| Model #:      |        |

## AF72 FREEZER

# THREE DOOR REACH-IN FREEZER



### AF72

- Tested to NSF Standard 7 requirements for open food storage
- Standard with full two year parts and labor warranties and a five year compressor warranty
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas







Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Nine adjustable, heavy-duty expoxy coated wire shelves.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Bottom mounted compressor for more efficient operation in coolest area of kitchen.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Electronic thermostat with external digital LED display for accurate control and easy reading.

Vaulted self closing doors that remain open at 90 degrees.

Magnetic door gasket is removable and replaceable without tools.

Freezer door frames have integral factory installed heating element to eliminate condensation.

Lockable door with foamed-in-place recessed handle.

Easy to mount plate casters (two lockable) are standard with all units.

Unit holds (3) full size sheet pans front to back. With (3) optional sls Pan Slide rack (#64900K). Some field install is required.


Tested to NSF Standard 7 requirements for open food storage.


Standard with full two year parts and labor warranties and a five year compressor warranty.


115V-230V/60Hz/1 -Nema L14-20P

#### STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

| Model<br>Number | Width | External D<br>Depth | imensions<br>Height* | Doors | Epoxy Coated<br>Shelves<br>(Horizontal) | Cubic<br>Feet | Temperature<br>Range | Cord<br>Length | НР   | AMPS | REF  | NEMA<br>Plug                       | Crate<br>Weight |
|-----------------|-------|---------------------|----------------------|-------|---|---------------|----------------------|----------------|------|------|------|------------------------------------|-----------------|
| AF72            | 81"   | 32"                 | 81.5"                | 3     | 9                                       | 72            | -10 F to 10 F        | 8′             | 1.25 | 6.2  | R290 | 115V-230V/60Hz/1 -<br>Nema L14-20P | 829lbs          |







Depth with door open 90 = 59.50"

