

Stainless design. Stellar performance. Superior value.

Project name: _	
Location:	
Item #:	_ QTY:
Model #:	

AR72 REFIGERATOR

THREE DOOR REACH-IN REFRIGERATOR



AR72

- ► Tested to NSF Standard 7 requirements for open food storage
- Standard with full two year parts and labor warranties and a five year compressor warranty
- Arctic Air products must pass numerous quality control inspections throughout the manufacturing process
- All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas

Energy Star approved









Exterior cabinet construction consists of full stainless steel front and sides.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Six adjustable, heavy-duty epoxy coated wire shelves.

Self-contained capillary tube system using environmentally friendly R290 Hydrocarbon gas.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Bottom mounted compressor for more efficient operation in coolest area of kitchen.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.



Electronic thermostat with external digital LED display for accurate control and easy reading.

Vaulted self closing doors that remain open at 90 degrees.

Magnetic door gasket is removable and replaceable without tools.

Lockable door with foamed-in-place recessed handle.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Easy to mount plate casters (two lockable) are standard with all units.


Unit can hold an additional (2) optional stainless steel full size sheet pan racks – part # 64900K behind each door, some field install is required.


Tested to NSF Standard 7 requirements for open food storage.


Standard with full two year parts and labor warranties and a five year compressor warranty.

STAINLESS STEEL DESIGN . STELLAR PERFORMANCE . SUPERIOR VALUE

Model Number	Width	External Di Depth	mensions Height*	Doors	Epoxy Coated Shelves (Horizontal)	Cubic Feet	Temperature Range	Cord Length	HP	AMPS	REF	NEMA Plug	Crate Weight	
AR72	81″	32"	81.5″	3	9	72	33°F to 41°F	8′	2/3	4.2	R290	115V/60Hz/1 - NEMA 5-15P	790lbs	







Depth with door open 90 = 59.50"

